



**PREP:** SELECT geared continuous hinges can be prepared for accessible electric through-wires to provide continuous current. Through-wires available in sets of 4, 8 or 12.

Per conductor: 12V-24V AC/DC at 3-6 amps. Ultra-flexible 22 gauge wire with 8" leads per leaf. Molex® connectors included. Connecting adaptors available as an option (see Electric Prep Accessories page).

**LOCATION:** Specify the dimension from the top of the hinge to each ATW centerline. Hinge is installed flush with the top of the door.

*Refer to the templates in the Concealed Geared Hinge section to choose from available ATW locations. These templates are also available online at [www.SelectHinges.com](http://www.SelectHinges.com).*

**HANDING:** Specify the handing of each door requiring the ATW. Handing not required on SL11 and SL27.

**ORDER:** Use suffix "ATW," plus the number of wires required. Specify location of each ATW and handing (if required).

*Example: SL24 HD 83" Clear ATW4 44-1/16" from top of hinge to centerline, RH.*

**NOTE:** For 90-degree openings, please specify at time of order for no upcharge. There will be an upcharge for 90-degree ATW cover plates when ordered separately and clear or bronze must be specified.

**AVAILABILITY:** Available on models SL11, SL12, SL14, SL18, SL24, SL26, SL27, SL31, SL44, SL48 and SL84.

Hinges with ATW prep can be ordered with a painted finish on the gear cap *only*.

**LEAD TIME:** 48 Hours (on most orders).

**WARRANTY:** 6 years.

**IMPORTANT:** SELECT Products Limited does not recommend preparing door and frame for ATW before receipt of hinge. If door and frame must be prepared before receipt of hinge, contact factory for special template.

