

Equip your toolbox with SELECT **PROBLEM-SOLVERS**



Speed up installations with these new solutions.

Whether you're renovating high-traffic entryways or putting in new frames and doors, you want your job to go faster and easier. Now there are six ways to simplify installing SELECT geared continuous hinges:

PIVOT HINGE HOLE COVERS

Instant improvement.

Mask the unsightly holes left by previous pivot hinge preps with SELECT's self-adhesive covers. Block out insects, dirt and water, too.



HB375 DRILL BIT

No center punch needed.


SELECT's .375-inch drill bit is designed specifically to speed up installation of our geared continuous hinges.



SHIM STOCK

Make invisible adjustments.

Square up doors and frames without ruining their appearance.



NEW! BUTT HINGE FILLER PLATES

Cutouts vanish.

Cover cutouts left by previous butt hinges with SELECT's self-adhesive filler plates. Break off the plate's excess polymer edges to fit each cutout's shape and size. Perfect for storefronts and hollow metal doors.



NEW! SELF-CENTERING HINGE BIT

Accurate alignment every time.

SELECT's self-centering hinge bit accurately drills pilot holes for self-tapping, thread-forming screws. The hex power bit fits all power bit and quick-change chucks for quick, precise performance.



NEW! MASONRY BIT

Faster drilling and longer life.

Designed for top performance, SELECT's masonry bit is perfectly fit to clear out behind hinge mounting screws (without damaging the mounting holes) in slush-filled (concrete) frames.

