


**Cutout for Von Duprin EPT2,  
EPT10, PN1, CEPT, ABH PT 200  
or ABH PT 1000**

**PREP:** SELECT geared continuous hinges can be prepared for the Von Duprin EPT2 and EPT10 power transfer unit and the Von Duprin PNT1 pneumatic transfer unit; others available upon request (please see template on following page). Contact factory for quotes and availability on preparations for power transfer units.

**LOCATION:** Specify the dimension from the top of the hinge to the centerline of the cutout. (Cutout length is 9-1/8"; centerline of the cutout is 4-9/16" from the top edge of cutout.) Hinge is installed flush with the top of the door.

*Refer to the templates in the Concealed or Half Surface Geared Hinge sections to avoid specifying a cutout location that cuts through fastener holes. These templates are also available online at [www.selecthinges.com](http://www.selecthinges.com).*

**HANDING:** Specify the handing of each door requiring the EPT. Handing not required on SL11 and SL27.

**ORDER:** Use suffix "VD-EPT" or "VD-PNT," plus the location and handing (if required).

*Example: SL24 HD600 83" Clear VD-EPT 41" from top of hinge to centerline, RH.*

**AVAILABILITY:** Available on geared hinge models SL11, SL12, SL14, SL18, SL24, SL26, SL27, SL31, SL40, SL41, SL44, SL48, SL52, SL53, SL54, SL77 and SL84. For the SL40 and SL41, please consult factory for engineering approval.

**LEAD TIME:** 48 hours (on most orders).

**IMPORTANT:** *SELECT Products Limited does not recommend preparing door and frame for EPT before receipt of hinge. If door and frame must be prepared before receipt of hinge, contact factory for special template.*