


SL14 95" HD600

All dimensions are measured in inches and [millimeters] from the top of the door to the centerline of the holes and ATW panels.

Choose location for ATW prep. ATW4 = 1 location; ATW8 = 1 location; and ATW12 = 1 location.

NOTE: For 90-degree openings, please specify at time of order for no upcharge. There will be an upcharge for 90-degree ATW cover plates when ordered separately and clear or bronze must be specified.

SL14 Profile



42 fasteners / 36 bearings

HOLES	ATW LOCATIONS
1 1/2 [38.1]	0 [0]
3 1/2 [88.9]	
5 1/2 [139.7]	
10 [254.0]	11 5/8 [295.3]
	14 3/16 [360.4]
	16 3/4 [425.5]
20 [508.0]	21 7/8 [555.6]
	24 7/16 [620.7]
	27 [685.8]
30 [762.0]	32 1/8 [816.0]
	34 11/16 [881.1]
	37 1/4 [946.2]
40 [1016.0]	42 3/8 [1076.3]
	44 15/16 [1141.4]
47 1/2 [1206.5]	50 1/16 [1271.6]
	52 5/8 [1336.7]
55 [1397.0]	57 3/4 [1466.9]
	60 5/16 [1532.0]
	62 7/8 [1597.0]
65 [1651.0]	68 [1727.2]
	70 9/16 [1792.3]
	73 1/8 [1857.4]
75 [1905.0]	78 1/4 [1987.6]
	80 13/16 [2052.6]
	83 3/8 [2117.7]
85 [2159.0]	
89 1/2 [2273.3]	
91 1/2 [2324.1]	
93 1/2 [2374.9]	
	95 [2413.0]